

Name: **VSM KK711X**

**1. Features:**

Grain: aluminium oxide  
Grit: P20, 24, 30, 36, 40, 50, 60, 80, 100, 120, 150, 180, 220, 240, 280, 320, 400  
Backing: sturdy polyester cloth (coarse up to and including P80)  
sturdy cotton cloth (P100 and finer)  
Bonding: resin over resin  
Width: 1480 mm (P20 - 180)  
1450 mm (P220 - 400)

**2. Application:**

Material: unalloyed and low alloy steel, cast irons, aluminium alloys, brass and bronze, hard carbide coatings , rubber and synthetic materials  
Workpiece: fittings, containers, cutlery, metal coils, surgical tools, castings, hand tools, tubes and rods (cylindrical/square) , forged parts, metal fabrications, furniture parts/metal  
Grinding process: cylindrical grinding, flat grinding  
Operation: automatic grinding, powertools, manual grinding / Backstand, robot grinding

**3. Advantages:**

- our main allround abrasive with a high cutting rate and good grinding performance
- cooling lubricant resistant up to and including P80

**4. Further information:**

**VSM · Vereinigte Schmirgel- und Maschinen-Fabriken AG**

Siegmundstr.17 · D-30165 Hannover  
P.O.B. 6107 · D-30061 Hannover  
Tel. + 49 511 3526 0 · Fax + 49 511 3526 315  
<http://www.vsmag.de> · e-mail: [info@vsmag.de](mailto:info@vsmag.de)